



## QM-13FB1000M: 13 oz. matte frontlit fire retardant scrim banner

Unlike most scrim banner on the market, 13FB1000M was developed to be extremely durable and work across Latex, Eco-Solvent and UV platforms. Its high tensile strength 1000 x 1000 denier scrim, makes for a very tear resistant banner. The fire retardant coating allows it to be used in all environments.



### Benefits:

- Fire Retardant
- 1000 x 1000 Denier
- Scratch Resistant
- Durable

### Applications:

- Frontlit Banners
- Display Systems
- Grommeted Banners
- POP Display

Registered Latex Developer

#### TECHNICAL DATA: QM-13FB1000M – 13 OZ. MATTE FRONTLIT FIRE RETARDANT SCRIM BANNER

SURFACE FINISH:	Matte	OPACITY:	100
BASE MATERIAL:	PVC	STORAGE:	Indoor 2 yrs. between 50-80°
BASE WEIGHT:	(13 oz.) 440 GSM +/- 10%	ROLL LENGTH:	150 FT.
CALIPER:	15 Mil +/- 1	ROLL WIDTHS:	38", 54" & 60"
BRIGHTNESS:	85 (ISO Blue Whiteness)	CORE:	3"
WHITENESS:	116 (CIE Ganz)	PRINT SIDE:	Print Side In
GLOSS MEASUREMENT	6 +/- 10% by angle of 60°	INK RECOMMENDATIONS:	ECO-SOLVENT  LATEX  UV



This media is designed for digital printing applications using OEM printers with their accompanying OEM ink sets. Although designed for all printers using the aforementioned OEM matching ink sets; actual results may vary depending on printer model, age, print design, environmental conditions, and other factors. Exposure of a print to atmospheric pollutants, or to temperature, humidity, and / or lighting extremes can result in fading, color shifting, or other visual changes. The ideal conditions for printing and storage are a temperature of 70°F ±5°F and relative humidity of 50% RH ±3% RH. Our wide format media is guaranteed against manufacturing flaws and defects and is designed to resist printer jams when used properly.