



QM-GLMP10: Professional gloss microporous RC photo paper

This true resin coated heavyweight photo paper allows for heavy ink saturation without cockling. It has an instant dry coating for fast production times and high gloss finish for professional results.




Benefits:

- Water Resistant
- High Gloss Finish
- True Resin Coated
- Instant Dry Coating

Applications:

- Framing
- Gallery Prints
- Photo Reproduction
- Posters / POP Displays

TECHNICAL DATA: QM-GLMP10 – PROFESSIONAL GLOSS MICROPOROUS RC PHOTO PAPER

| | | | |
|-----------------|--------------------------|---------------------|---|
| SURFACE FINISH: | High Gloss | GLOSS MEASUREMENT: | 48 +/- 10% by angle of 60° |
| BASE MATERIAL: | Paper | STORAGE LIFE: | 3 Yrs. Below 100° F / RH Below 40% |
| BASE WEIGHT: | 260 GSM +/- 10% | ROLL LENGTH: | 100 FT. |
| CALIPER: | 10 MIL +/- 1 | ROLL WIDTHS: | 24", 36", 42", 50", 60" |
| BRIGHTNESS: | 103 (ISO Blue Whiteness) | CORE: | 3" with 2" Adapter |
| WHITENESS: | 154 (CIE Ganz) | PRINT SIDE: | Print Side Only |
| OPACITY: | 97 | INK RECOMENDATIONS: |  AQUEOUS |



This media is designed for digital printing applications using OEM printers with their accompanying OEM ink sets. Although designed for all printers using the aforementioned OEM matching ink sets; actual results may vary depending on printer model, age, print design, environmental conditions, and other factors. Exposure of a print to atmospheric pollutants, or to temperature, humidity, and / or lighting extremes can result in fading, color shifting, or other visual changes. The ideal conditions for printing and storage are a temperature of 70°F ±5°F and relative humidity of 50% RH ±3% RH. Our wide format media is guaranteed against manufacturing flaws and defects and is designed to resist printer jams when used properly.

