



## QM-LABOB2S: Premium matte double-sided hybrid blackout film

This rich, double sided Latex printable media shows exceptionally well in banner stand & window mounted signage applications. Perfect for double sided window mounted graphics when paired with QM-WINDOWMT.



### Benefits:

- Tear Resistant
- Good Rigidity
- Double Sided Latex Printing

### Applications:

- Sun Blocking Signage
- Roll-up Banners
- Indoor/Outdoor Mounted Signage

Registered Latex Developer

#### TECHNICAL DATA: QM-LABOB2S – PREMIUM MATTE DOUBLE-SIDED HYBRID BLOCKOUT FILM

SURFACE FINISH:	Matte	WHITENESS:	77 (CIE Ganz)
BASE MATERIAL:	Hybrid Film	GLOSS MEASUREMENT	2.2 +/- 0.5% by angle of 60°
ADHESIVE:	N/A	OPACITY:	100
LINER MATERIAL:	N/A	STORAGE:	Indoor 2 yrs. between 50-80°
LINER WEIGHT	N/A GSM +/- 10%	ROLL LENGTH:	100 FT.
LINER THICKNESS:	N/A Mil +/- 1	ROLL WIDTHS:	36" and 60"
FACE STOCK WEIGHT:	222 GSM +/- 10%	CORE:	3" with 2" Adapter
FACE STOCK THICKNESS	9 Mil +/- 1	PRINT SIDE:	Print Side Out
BRIGHTNESS:	87 (ISO Blue Whiteness)	INK RECOMMENDATIONS:	LATEX  UV



This media is designed for digital printing applications using OEM printers with their accompanying OEM ink sets. Although designed for all printers using the aforementioned OEM matching ink sets; actual results may vary depending on printer model, age, print design, environmental conditions, and other factors. Exposure of a print to atmospheric pollutants, or to temperature, humidity, and / or lighting extremes can result in fading, color shifting, or other visual changes. The ideal conditions for printing and storage are a temperature of 70°F ±5°F and relative humidity of 50% RH ±3% RH. Our wide format media is guaranteed against manufacturing flaws and defects and is designed to resist printer jams when used properly.