



QM-LABOB2S: Hybrid matte double-sided blackout film

This rich, double sided Latex printable media shows exceptionally well in banner stand & window mounted signage applications. Perfect for double sided window mounted graphics when paired with QM-WINDOWMT.



Benefits:

- Tear Resistant
- Good Rigidity
- Double Sided Latex Printing

Applications:

- Sun Blocking Signage
- Roll-up Banners
- Indoor/Outdoor Mounted Signage

Registered Latex Developer

TECHNICAL DATA: QM-LABOB2S – HYBRID MATTE DOUBLE-SIDED BLOCKOUT FILM

SURFACE FINISH:	Matte	OPACITY:	100
BASE MATERIAL:	Hybrid Film	STORAGE:	Indoor 2 yrs. between 50-80°
BASE WEIGHT:	203 GSM +/- 10%	ROLL LENGTH:	100 FT.
CALIPER:	10 Mil +/- 1	ROLL WIDTHS:	36" & 60"
BRIGHTNESS:	85 (ISO Blue Whiteness)	CORE:	3" with 2" Adapter
WHITENESS:	75 (CIE Ganz)	PRINT SIDE:	Print Side Out
GLOSS MEASUREMENT	2.2 +/- 10% by angle of 60°	INK RECOMMENDATIONS:	Latex UV



This media is designed for digital printing applications using OEM printers with their accompanying OEM ink sets. Although designed for all printers using the aforementioned OEM matching ink sets; actual results may vary depending on printer model, age, print design, environmental conditions, and other factors. Exposure of a print to atmospheric pollutants, or to temperature, humidity, and / or lighting extremes can result in fading, color shifting, or other visual changes. The ideal conditions for printing and storage are a temperature of 70°F ±5°F and relative humidity of 50% RH ±3% RH. Our wide format media is guaranteed against manufacturing flaws and defects and is designed to resist printer jams when used properly.

