



# Magnate

Solvent, Eco Solvent, Latex, UV Media



## QM-MAXVUE: Mesh Banner with Liner

Our 14 mil mesh banner with liner is reinforced with polyester scrim for added durability. The liner makes the printing process easier by preventing ink spray through and helping the media to feed easily through the printer. special liner for easy removal after high heat Latex printing.



### Benefits:




- Tiny perforations decrease wind resistance
- Perfect for indoor & outdoor use
- Water resistant
- Ultra Strong

### Applications:

- Outdoor Banners
- Window Signage
- Large advertisements where a "see through" effect is needed
- Job Site Signage

Registered Latex Developer 

#### TECHNICAL DATA: QM-MAXVUE-MESH BANNER WITH LINER

|                    |                               |                      |  |
|--------------------|-------------------------------|----------------------|--|
| SURFACE FINISH:    | Mesh White Gloss              | OPACITY:             | 50/50  |
| BASE MATERIAL:     | Textile                       | STORAGE:             | Indoor 3 yrs. between 50-80°   |
| BASE WEIGHT:       | 244 GSM +/- 10%               | ROLL LENGTH:         | 150 FT.  |
| CALIPER:           | 14 Mil +/- 1                  | ROLL WIDTHS:         | 38" & 60"  |
| BRIGHTNESS:        | 81 (ISO Blue Whiteness)       | CORE:                | 3"   |
| WHITENESS:         | 103 (CIE Ganz)                | PRINT SIDE:          | Print Side Out   |
| GLOSS MEASUREMENT: | 15-22 +/- 10% by angle of 60° | INK RECOMMENDATIONS: |  ECO-SOLVENT  LATEX  UV |



This media is designed for digital printing applications using OEM printers with their accompanying OEM ink sets. Although designed for all printers using the aforementioned OEM matching ink sets; actual results may vary depending on printer model, age, print design, environmental conditions, and other factors. Exposure of a print to atmospheric pollutants, or to temperature, humidity, and / or lighting extremes can result in fading, color shifting, or other visual changes. The ideal conditions for printing and storage are a temperature of 70°F ±5°F and relative humidity of 50% RH ±3% RH. Our wide format media is guaranteed against manufacturing flaws and defects and is designed to resist printer jams when used properly.