



QM-PFH: Heavy weight matte WR coated fabric

This heavy 100% polyester fabric can be used for many different applications, and with a consistent, tight weave pattern, PFH has the special ability to resist feed bunching. Graded heavy weight fabric at 300 Denier, PFH can easily be recycled, making it an eco-friendly printing solution.



Benefits:

- 100% Polyester
- 300 x 300 Denier
- Matte Finish
- Recyclable

Applications:

- Indoor/Outdoor Hanging Flags
- Decorative POS/POP Displays
- Soft Signage
- Decor Faux Canvas Prints

Registered Latex Developer



TECHNICAL DATA: QM-PFH – HEAVY WEIGHT MATTE WR COATED FABRIC

SURFACE FINISH:	Matte	OPACITY:	82
BASE MATERIAL:	Polyester	STORAGE:	Indoor 3 yrs. between 50-80° and below 40% RH
FABRIC WEAVE:	300 x 300d	ROLL LENGTH:	150 FT.
BASE WEIGHT:	163 GSM +/- 10%	ROLL WIDTHS:	24", 36", 50" & 60"
CALIPER:	9 Mil +/- 1	CORE:	3" Core with 2" Adapter
BRIGHTNESS:	93 (ISO Blue Whiteness)	PRINT SIDE:	Print Side Out
WHITENESS:	128 (CIE Ganz)	INK RECOMMENDATIONS:	AQUEOUS LATEX UV
GLOSS MEASUREMENT	3 +/- 10% by angle of 60°		



This media is designed for digital printing applications using OEM printers with their accompanying OEM ink sets. Although designed for all printers using the aforementioned OEM matching ink sets; actual results may vary depending on printer model, age, print design, environmental conditions, and other factors. Exposure of a print to atmospheric pollutants, or to temperature, humidity, and / or lighting extremes can result in fading, color shifting, or other visual changes. The ideal conditions for printing and storage are a temperature of 70°F ±5°F and relative humidity of 50% RH ±3% RH. Our wide format media is guaranteed against manufacturing flaws and defects and is designed to resist printer jams when used properly.