



Motif

Aqueous Specialty Media



QM-PFL: Ultra Light Matte Coated Fabric

This versatile ultra light 100% polyester fabric can be used for many different applications, roll-up banners, hanging fabric banners, trade show displays, and durable flags. With a consistent, tight weave pattern, PFL has the special ability to resist feed bunching. Graded light weight fabric at 150 Denier, PFL can easily be recycled, making it an eco-friendly printing solution.



Benefits:

- 100% Polyester
- 150 x 150 Denier
- Matte Finish
- Recyclable

Applications:

- Indoor/Outdoor Hanging Flags
- Decorative POS & POP Displays
- Roll-Up Banners
- Soft Signage

Registered Latex Developer



TECHNICAL DATA: QM-PFL – ULTRA LIGHT MATTE COATED FABRIC

SURFACE FINISH:	Matte	OPACITY:	80%
FABRIC WEAVE:	150 x 150D	STORAGE:	Indoor 2 yrs. between 50-80°
BASE MATERIAL:	Polyester	ROLL LENGTH:	150 FT.
BASE WEIGHT:	147 GSM +/- 10%	ROLL WIDTHS:	36", 42", 50", & 60"
CALIPER:	8 Mil +/- 1	CORE:	3" Core with 2" Adapter
BRIGHTNESS:	96 (ISO Blue Whiteness)	PRINT SIDE:	Print Side Out
WHITENESS:	120 (CIE Ganz)	INK RECOMMENDATIONS:	AQ AQUEOUS L LATEX UV UV
GLOSS MEASUREMENT	3 +/- 10% by angle of 60° of Gloss Meter		



This media is designed for digital printing applications using OEM printers with their accompanying OEM ink sets. Although designed for all printers using the aforementioned OEM matching ink sets; actual results may vary depending on printer model, age, print design, environmental conditions, and other factors. Exposure of a print to atmospheric pollutants, or to temperature, humidity, and / or lighting extremes can result in fading, color shifting, or other visual changes. The ideal conditions for printing and storage are a temperature of 70°F ±5°F and relative humidity of 50% RH ±3% RH. Our wide format media is guaranteed against manufacturing flaws and defects and is designed to resist printer jams when used properly.