



PPGWRAD: Professional gloss microporous polypropylene w/ permanent adhesive

This is our highest quality polypropylene for indoor film signage, it has high adhesion and requires little maintenance. Its microporous coating gives it the ability to reproduce photo quality images while maintaining superior tear resistance.



Benefits:

- Water Resistant
- High Gloss Finish
- High Color Gamut with Instant Dry Coating
- Tear Resistant


Applications:

- Window Signage
- Boards and Magnate Material
- Photo Reproduction
- Best for Non Laminated Applications

Registered Latex Developer



TECHNICAL DATA: QM-PPGWRAD – PROFESSIONAL GLOSS MICROPOROUS POLYPROPYLENE W/ PERMANENT ADHESIVE

SURFACE FINISH:	Gloss	OPACITY:	97
BASE MATERIAL:	Polypropylene	STORAGE:	Indoor, 1 yr. between 50-80°
BASE WEIGHT:	145 GSM +/- 10%	SERVICE LIFE:	Indoor 6 mo./outdoor 3 mo.
CALIPER:	5 MIL +/- 1	ROLL LENGTH:	100 FT.
LINER:	PE Coated Silicone Paper	ROLL WIDTHS:	36", 50", 60"
BRIGHTNESS:	94 (ISO Blue Whiteness)	CORE:	2"
WHITENESS:	110 (CIE Ganz)	PRINT SIDE:	Print Side Out
GLOSS MEASUREMENT:	34 +/- 10% by angle of 60°	INK RECOMENDATIONS:	 AQUEOUS



This media is designed for digital printing applications using OEM printers with their accompanying OEM ink sets. Although designed for all printers using the aforementioned OEM matching ink sets; actual results may vary depending on printer model, age, print design, environmental conditions, and other factors. Exposure of a print to atmospheric pollutants, or to temperature, humidity, and / or lighting extremes can result in fading, color shifting, or other visual changes. The ideal conditions for printing and storage are a temperature of 70°F ±5°F and relative humidity of 50% RH ±3% RH. Our wide format media is guaranteed against manufacturing flaws and defects and is designed to resist printer jams when used properly.

