




QM-PROWRPPAD: Professional high speed matte polypropylene w/ permanent adhesive and anti-slip PET liner

Specifically designed to work with high speed printers and legacy printers with slightly worn pinch rollers. Our 8mil polypropylene has an instant dry, bright white, matte, water resistant coating, and an anti-slip PET liner that keeps production moving. Our coating accepts high ink loads for cleaner, crisper details. Use for any flat-mounted applications



Benefits:

- Water Resistant
- Non-Glare Matte Finish
- Tear Resistant
- High Speed Printing

Applications:

- Board
- Windows
- Packaging Prototypes
- Event Graphics & Posters

Registered Latex Developer



TECHNICAL DATA: QM-PROWRPPAD – PROFESSIONALHIGH SPEED MATTE POLYPROPYLENE W/ PERMANENT ADHESIVE AND ANTI-SLIP PET LINER

SURFACE FINISH:	Matte	WHITENESS:	125 (CIE Ganz)
BASE MATERIAL:	Polypropylene	OPACITY:	96
ADHESIVE:	Permanent Clear Acrylic	STORAGE:	Indoor, 3 yrs. between 50-80° and below 40° RH
LINER WIEGHT:	42 GSM +/- 10%	ROLL LENGTH:	100 FT.
LINER THICKNESS:	1.2 Mil +/- 1	ROLL WIDTHS:	36", 50"
FACE STOCK WEIGHT:	120 GSM +/- 10%	CORE:	3"
FACE STOCK CALIPER:	8 Mil	PRINT SIDE:	Print Side Out
BRIGHTNESS:	108 (ISO Blue Whiteness)	INK RECOMENDATIONS:	AQUEOUS UV LATEX



This media is designed for digital printing applications using OEM printers with their accompanying OEM ink sets. Although designed for all printers using the aforementioned OEM matching ink sets; actual results may vary depending on printer model, age, print design, environmental conditions, and other factors. Exposure of a print to atmospheric pollutants, or to temperature, humidity, and / or lighting extremes can result in fading, color shifting, or other visual changes. The ideal conditions for printing and storage are a temperature of 70°F ±5°F and relative humidity of 50% RH ±3% RH. Our wide format media is guaranteed against manufacturing flaws and defects and is designed to resist printer jams when used properly.