




## QM-PV1: Perforated vinyl 60/40 ratio w/ removable adhesive paper liner

PV1 has the right amount of vinyl for optimum graphic, 60% and the perfect amount of perforation for outside view, 40%. Exterior window mount perforated 7 mil calendared white vinyl with removable adhesive. Comes with paper liner and is durable enough to last 3 years outdoor.



Hole Size: 1.6 mm, Perf Ratio of 42.94%



### Benefits:

- Easy Application
- Removable
- Vivid Graphics


### Applications:

- Retail/Commercial Signage
- Decals
- Window Posters

Registered Latex Developer



#### TECHNICAL DATA: QM-PV1 – PERFORATED VINYL 60/40 RATIO W/ REMOVABLE ADHESIVE PAPER LINER

SURFACE FINISH:	Gloss	WHITENESS:	89 (CIE Ganz)
BASE MATERIAL:	PVC	STORAGE:	Indoor, 1 yr. between 75° 50-60% RH
ADHESIVE MATERIAL:	Clear Acrylic Pressure Sensitive Adhesive	OPACITY:	60% Printable / 40% Viewable
LINER MATERIAL:	Single side PE Coated White Wood-pulp Paper	ROLL LENGTH:	164 FT.
LINER WEIGHT:	145 GSM +/- 10%	ROLL WIDTHS:	54" & 60"
LINER CALIPER:	6 Mil +/- 1	CORE:	3"
FACE STOCK WEIGHT:	145 GSM +/- 10%	PRINT SIDE:	Print Side Out
FACE STOCK CALIPER:	7 Mil +/- 1	INK RECOMMENDATIONS:	 ECO-SOLVENT



This media is designed for digital printing applications using OEM printers with their accompanying OEM ink sets. Although designed for all printers using the aforementioned OEM matching ink sets; actual results may vary depending on printer model, age, print design, environmental conditions, and other factors. Exposure of a print to atmospheric pollutants, or to temperature, humidity, and / or lighting extremes can result in fading, color shifting, or other visual changes. The ideal conditions for printing and storage are a temperature of 70°F ±5°F and relative humidity of 50% RH ±3% RH. Our wide format media is guaranteed against manufacturing flaws and defects and is designed to resist printer jams when used properly.