



QM-SGV: Everyday gloss vinyl w/ permanent adhesive

SGV is your best option for everyday use. It's bright white surface provides the best color graphics and it's improved double-side PE coated liner makes for easy installations. The solvent acrylic adhesive provides longer term adhesion. This product is sure to be your go-to for most mounted jobs.



Benefits:




- Bright White
- High Gloss
- Easy Application

Applications:

- Floor Graphics
- Flexible or Mounted Signage
- Trade Show Graphics

Registered Latex Developer 

TECHNICAL DATA: QM-SGV – EVERYDAY GLOSS VINYL W/ PERMANENT ADHESIVE

SURFACE FINISH:	Gloss	OPACITY:	95
BASE MATERIAL:	PVC	GLOSS MEASUREMENT:	28 +/- 10% by angle of 60°
ADHESIVE MATERIAL:	Clear solvent acrylic PSA	STORAGE LIFE:	1 yr. at 75° and 50-60% RH
LINER MATERIAL:	Double-side PE coated white Wood-pulp Paper	LAMINATION:	Que Media Laminates Recommended
LINER WEIGHT:	160 GSM +/- 10%	ROLL LENGTH:	150 Ft.
LINER CALIPER:	6 Mil +/- 1	ROLL WIDTHS:	30", 48", 54" & 60"
FACE STOCK WEIGHT:	165 GSM +/- 10%	CORE:	3"
FACE STOCK CALIPER:	4.5 Mil +/- 1	PRINT SIDE:	Print Side Out
BRIGHTNESS:	96 (ISO Blue Whiteness):	INK RECOMENDATIONS:	 ECO-SOLVENT  LATEX  UV
WHITENESS:	150 (CIE Ganz)		



This media is designed for digital printing applications using OEM printers with their accompanying OEM ink sets. Although designed for all printers using the aforementioned OEM matching ink sets; actual results may vary depending on printer model, age, print design, environmental conditions, and other factors. Exposure of a print to atmospheric pollutants, or to temperature, humidity, and / or lighting extremes can result in fading, color shifting, or other visual changes. The ideal conditions for printing and storage are a temperature of 70°F ±5°F and relative humidity of 50% RH ±3% RH. Our wide format media is guaranteed against manufacturing flaws and defects and is designed to resist printer jams when used properly.