



SGVBF: Bubble free vinyl w/ removable adhesive

SGVBF has a heavy stay-flat coated liner and air egress technology allowing for easy application and removal. Solid grey, removable adhesive to blockout anything under the graphic and add color “pop”. Use on windows or any smooth mounting surface. This product works extremely well with all print and cut systems.



Benefits:

- Improved PE Coated Liner
- Easy Application & Clean Removal
- For Indoor/Outdoor Use
- High White Point

Applications:

- Window Display
- Decals
- Rigid Board

Registered Latex Developer



TECHNICAL DATA: QM-SGVBF – BUBBLE FREE VINYL W/ REMOVABLE ADHESIVE

| | | | |
|---------------------|--|---------------------|--|
| SURFACE FINISH: | Gloss | OPACITY: | 98 |
| BASE MATERIAL: | PVC | GLOSS MEASUREMENT: | 55 +/- 10% by angle of 60° |
| ADHESIVE MATERIAL: | Removable Grey Acrylic | STORAGE LIFE: | Indoor/outdoor 6 months to 1 yr (55*-85°F) |
| LINER MATERIAL: | Double Sided PE Coated White Wood Pulp Paper | LAMINATION: | Que Media Lamination Recommended |
| LINER WEIGHT: | 146 GSM +/- 10% | ROLL LENGTH: | 150 Ft. |
| LINER CALIPER: | 7 Mil +/- 1 | ROLL WIDTHS: | 54" |
| FACE STOCK WEIGHT: | 160 GSM +/- 10% | CORE: | 3" |
| FACE STOCK CALIPER: | 4.5 Mil +/- 1 | PRINT SIDE: | Print Side Out |
| BRIGHTNESS: | 88 (ISO Blue Whiteness) | INK RECOMENDATIONS: | ES ECO-SOLVENT L LATEX UV UV |
| WHITENESS: | 143 (CIE Ganz) | | |



This media is designed for digital printing applications using OEM printers with their accompanying OEM ink sets. Although designed for all printers using the aforementioned OEM matching ink sets; actual results may vary depending on printer model, age, print design, environmental conditions, and other factors. Exposure of a print to atmospheric pollutants, or to temperature, humidity, and / or lighting extremes can result in fading, color shifting, or other visual changes. The ideal conditions for printing and storage are a temperature of 70°F ±5°F and relative humidity of 50% RH ±3% RH. Our wide format media is guaranteed against manufacturing flaws and defects and is designed to resist printer jams when used properly.