



Magnate

Solvent, Eco Solvent, Latex, UV Media



QM-SOLPPM: Eco-solvent Matte Polypropylene Film

This 7 mil polypropylene, SOLPPM has good water and tear resistance. It's smooth matte, microporous top coating gives it the ability to reproduce rich, accurate color. This is an ideal product for indoor or outdoor signage. SOLPPM has been designed for eco-solvent, latex and UV inks.



Benefits:

- Tear Resistant
- Water Resistant
- Non-glare Matte Finish
- Economical

Applications:

- POP Display
- Indoor/Outdoor Banner
- Posters

Registered Latex Developer



TECHNICAL DATA: SOLPPM – ECO-SOLVENT MATTE POLYPROPYLENE FILM

| | | | |
|-------------------|---------------------------|---------------------|------------------------------|
| SURFACE FINISH: | Matte | OPACITY: | 96% |
| BASE MATERIAL: | Polypropylene | STORAGE: | Indoor 2 yrs. between 50-80° |
| BASE WEIGHT: | 155 GSM +/- 10% | ROLL LENGTH: | 100 FT. |
| CALIPER: | 7 Mil +/- 1 | ROLL WIDTHS: | 36" & 60" |
| BRIGHTNESS: | 102 (ISO Blue Whiteness) | CORE: | 3" |
| WHITENESS: | 126 (CIE Ganz) | PRINT SIDE: | Print Side Out |
| GLOSS MEASUREMENT | 6 +/- 10% by angle of 60° | INK RECOMENDATIONS: | ECO-SOLVENT LATEX UV |



This media is designed for digital printing applications using OEM printers with their accompanying OEM ink sets. Although designed for all printers using the aforementioned OEM matching ink sets; actual results may vary depending on printer model, age, print design, environmental conditions, and other factors. Exposure of a print to atmospheric pollutants, or to temperature, humidity, and / or lighting extremes can result in fading, color shifting, or other visual changes. The ideal conditions for printing and storage are a temperature of 70°F ±5°F and relative humidity of 50% RH ±3% RH. Our wide format media is guaranteed against manufacturing flaws and defects and is designed to resist printer jams when used properly.