



# Magnate

Solvent, Eco Solvent, Latex, UV Media



## QM-SWRPPBO: Satin Hybrid Blockout Polypropylene

Bright white satin top coating for bright color graphic printing. The block-out layer give your graphic “POP” with no wash-out from the backside. The back side coating creates a economical product with good stay-flatness. The perfect solution to short-term trade show displays and posters.



### Benefits:

- Instant Dry for Immediate Production Times
- Water & scratch Resistant
- Tear Resistant
- 100% Opaque

### Applications:

- Window Application with Mounting Adhesive
- Durable Posters
- Trade Show Display
- Low Cost Roll-Up

Registered Latex Developer



### TECHNICAL DATA: QM-SWRPPBO – SATIN HYBRID BLOCKOUT POLYPROPYLENE

SURFACE FINISH:	Satin	OPACITY:	100%
BASE MATERIAL:	Polypropylene	STORAGE:	Indoor 2 yrs. between 50-80°
BASE WEIGHT:	120 GSM +/- 10%	ROLL LENGTH:	100 FT.
CALIPER:	8 Mil +/- 1	ROLL WIDTHS:	36", 60"
BRIGHTNESS:	90 (ISO Blue Whiteness)	CORE:	3"
WHITENESS:	97 (CIE Ganz)	PRINT SIDE:	Print Side Out
GLOSS MEASUREMENT	13 +/- 10% by angle of 60°	INK RECOMMENDATIONS:	ECOSOLVENT  LATEX  UV



This media is designed for digital printing applications using OEM printers with their accompanying OEM ink sets. Although designed for all printers using the aforementioned OEM matching ink sets; actual results may vary depending on printer model, age, print design, environmental conditions, and other factors. Exposure of a print to atmospheric pollutants, or to temperature, humidity, and / or lighting extremes can result in fading, color shifting, or other visual changes. The ideal conditions for printing and storage are a temperature of 70°F ±5°F and relative humidity of 50% RH ±3% RH. Our wide format media is guaranteed against manufacturing flaws and defects and is designed to resist printer jams when used properly.