



QM-WRPPAD: Everyday matte polypropylene w/ permanent adhesive

Our #1 selling item, high performing matte polypropylene that can accept high ink loads and produce exceptional color graphics and detail. Best used on any fat mounted surface, easier than vinyl to apply due to the rigidity.



Benefits:

- Water Resistant
- Non-Glare Matte Finish
- Tear Resistant
- Economical

Applications:

- Best for Flat Mounting
- Mounting to Rigid Board or Windows
- Decals and POP Signage

Registered Latex Developer



TECHNICAL DATA: QM-WRPPAD – EVERYDAY MATTE POLYPROPYLENE W/ PERMANENT ADHESIVE

| | | | |
|---------------------|--------------------------|---------------------|------------------------------------------------|
| SURFACE FINISH: | Matte | WHITENESS: | 140 (CIE Ganz) |
| BASE MATERIAL: | Polypropylene | OPACITY: | 96 |
| ADHESIVE: | Permanent Clear Acrylic | STORAGE: | Indoor, 3 yrs. between 50-80° and below 40° RH |
| LINER WIEGHT: | 36 GSM +/- 10% | ROLL LENGTH: | 100 FT. |
| LINER THICKNESS: | 1 Mil +/- 1 | ROLL WIDTHS: | 24", 36", 42", 50", 60" |
| FACE STOCK WEIGHT: | 120 GSM +/- 10% | CORE: | 2" |
| FACE STOCK CALIPER: | 8 Mil | PRINT SIDE: | Print Side Out |
| BRIGHTNESS: | 108 (ISO Blue Whiteness) | INK RECOMENDATIONS: | AQUEOUS UV LATEX |



This media is designed for digital printing applications using OEM printers with their accompanying OEM ink sets. Although designed for all printers using the aforementioned OEM matching ink sets; actual results may vary depending on printer model, age, print design, environmental conditions, and other factors. Exposure of a print to atmospheric pollutants, or to temperature, humidity, and / or lighting extremes can result in fading, color shifting, or other visual changes. The ideal conditions for printing and storage are a temperature of 70°F ±5°F and relative humidity of 50% RH ±3% RH. Our wide format media is guaranteed against manufacturing flaws and defects and is designed to resist printer jams when used properly.