



QM-WRPPBO: Hybrid matte blackout stay-flat polypropylene

Smooth, matte porous top coating will not only allow for heavy ink saturation with aqueous inks but works extremely well with latex and UV inks producing vivid graphics. The blackout layer keeps your display bright with no wash-out. The perfect solution to short-term trade show displays and posters.



Benefits:

- Instant Dry Coating for Fast Production Times
- Water Resistant
- Good Tear Resistant
- 100% Opaque

Applications:

- Window Application with Mounting Adhesive
- Durable Posters
- Trade Show Display
- Low Cost Roll-Up

Registered Latex Developer

TECHNICAL DATA: QM-WRPPBO – HYBRID MATTE BLOCKOUT STAY-FLAT POLYPROPYLENE

SURFACE FINISH:	Matte	DURABILITY:	<i>Indoor:</i> Up to 1 year <i>Outdoor:</i> Up to 6 months
BASE MATERIAL:	Hybrid	GLOSS MEASUREMENT:	2 +/- 10% by angle of 60°
BASE WEIGHT:	185 GSM +/- 10%	ROLL LENGTH:	100 FT.
CALIPER (mil):	8 +/- 1	ROLL WIDTHS:	36", 42", & 60"
BRIGHTNESS:	96 (ISO Blue Whiteness)	CORE:	3" with 2" Adapter
WHITENESS:	125 (CIE Ganz)	PRINT SIDE:	Print Side Out
OPACITY:	100	INK RECOMMENDATIONS:	AQUEOUS UV LATEX



This media is designed for digital printing applications using OEM printers with their accompanying OEM ink sets. Although designed for all printers using the aforementioned OEM matching ink sets; actual results may vary depending on printer model, age, print design, environmental conditions, and other factors. Exposure of a print to atmospheric pollutants, or to temperature, humidity, and / or lighting extremes can result in fading, color shifting, or other visual changes. The ideal conditions for printing and storage are a temperature of 70°F ±5°F and relative humidity of 50% RH ±3% RH. Our wide format media is guaranteed against manufacturing flaws and defects and is designed to resist printer jams when used properly. Storage: Up to one year if stored in proper conditions (cool, dry place 50-80°)

