



QM-SMV: Everyday matte vinyl w/ permanent adhesive

SMV has clear, permanent, pressure sensitive adhesive and is designed for Eco-Solvent, UV and Latex-based inkjet printing. This high quality, budget friendly film can be used for promotional grade graphics, such as signs, decals and POP displays. Matte finish.



Benefits:

- Excellent Color Reproduction
- For Indoor/Outdoor Use
- Bright White for Image Pop

Applications:

- POP Display
- Flexible or Rigid Mounted Signage
- Decals

Registered Latex Developer



TECHNICAL DATA: QM-SMV – EVERYDAY MATTE VINYL W/ PERMANENT ADHESIVE

SURFACE FINISH:	Matte	WHITENESS:	148 (CIE Ganz)
BASE MATERIAL:	PVC	OPACITY:	94
ADHESIVE MATERIAL:	Hi Grade Permanent Acrylic Pressure Sensitive Adhesive	GLOSS MEASUREMENT:	6 +/- 10% by angle of 60°
LINER MATERIAL:	Double-side PE coated white Wood-pulp Paper	DURABILITY:	Indoor: Up to 1 year Outdoor: Up to 6 months
LINER WEIGHT:	160 GSM +/- 10%	ROLL LENGTH:	150 Ft.
LINER CALIPER:	6 Mil +/- 1	ROLL WIDTHS:	38", 54", & 60"
FACE STOCK WEIGHT:	165 GSM +/- 10%	CORE:	3"
FACE STOCK CALIPER:	4.5 Mil +/- 1	PRINT SIDE:	Print Side Out
BRIGHTNESS:	98 (ISO Blue Whiteness)	INK RECOMENDATIONS:	ES ECO-SOLVENT L LATEX UV UV
STORAGE:	Up to six months if stored in proper conditions (cool, dry place 50-80°)		



This media is designed for digital printing applications using OEM printers with their accompanying OEM ink sets. Although designed for all printers using the aforementioned OEM matching ink sets; actual results may vary depending on printer model, age, print design, environmental conditions, and other factors. Exposure of a print to atmospheric pollutants, or to temperature, humidity, and / or lighting extremes can result in fading, color shifting, or other visual changes. The ideal conditions for printing and storage are a temperature of 70°F ±5°F and relative humidity of 50% RH ±3% RH. Our wide format media is guaranteed against manufacturing flaws and defects and is designed to resist printer jams when used properly. Storage: Up to six months if stored in proper conditions (cool, dry place 50-80°)

