

Super heavy weight matte WR coated fabric

This fabric has a rich weave pattern that looks and feels expensive. This super heavy 100% polyester fabric is very versatile, and can be used for almost any application. Its pronounced weave and strong 600x600 denier makes it a great option for banners and also decor art printing. It can easily be recycled, making a great eco-friendly soft signage solution.



Benefits:

- 100% Polyester Fabric
- Canvas-Like Weave
- Ultra Strong
- Recyclable

Applications:

- Hanging Banners or Wall Drape
- Roll Up Banners
- Canvas Alternative
- Theater Backdrops

| TECHNICAL DATA: SUPER HEAVY WEIGHT MATTE WR COATED FABRIC | | | |
|---|---------------------------|----------------------|--|
| SURFACE FINISH: | Matte | OPACITY: | 85 |
| BASE MATERIAL: | Polyester | DURABILITY: | Indoor: Up to 1 year Outdoor: 6 months |
| FABRIC WEAVE: | 600D x 600D | ROLL LENGTH: | 100 FT. |
| BASE WEIGHT: | 240 GSM +/- 10% | ROLL WIDTHS: | 24", 36", 42", & 60" |
| CALIPER: | 13 Mil +/- 1 | CORE: | 3" with 2" adapter |
| BRIGHTNESS: | 94 (ISO Blue Whiteness) | PRINT SIDE: | Print Side Out |
| WHITENESS: | 125 (CIE Ganz) | INK RECOMMENDATIONS: | AQUEOUS LATEX UVUV |
| GLOSS MEASUREMENT | 3 +/- 10% by angle of 60° | | |



This media is designed for digital printing applications using OEM printers with their accompanying OEM ink sets. Although designed for all printers using the aforementioned OEM matching ink sets; actual results may vary depending on printer model, age, print design, environmental conditions, and other factors. Exposure of a print to atmospheric pollutants, or to temperature, humidity, and / or lighting extremes can result in fading, color shifting, or other visual changes. The ideal conditions for printing and storage are a temperature of 70°F ±5°F and relative humidity of 50% RH ±3% RH. Our wide format media is guaranteed against manufacturing flaws and defects and is designed to resist printer jams when used properly. Storage: Up to one year if stored in proper conditions (cool, dry place 50-80°)