



Everyday satin microporous RC instant dry photo paper

This photo paper is 200 GSM and has a true RC/microporous coating for instant-dry results. The coating allows users to print with heavy ink loads while maintaining sharp resolution. Ideal for just about any photo paper application, and priced aggressively enough to also handle proofing.





Benefits:

- Economical
- Professional Low Glare Finish
- Fast Dry Time

Applications:

- Posters
- Photo and Graphic Displays
- Photo Frame Applications

TECHNICAL DATA: EVERYDAY SATIN MICROPOROUS RC INSTANT DRY PHOTO PAPER

| | | | |
|--------------------|------------------------------|----------------------|--|
| SURFACE FINISH: | Satin | OPACITY: | 92 |
| BASE MATERIAL: | Paper | DURABILITY: | Indoor: Up to 1 year Outdoor: 6 months |
| BASE WEIGHT: | 200 GSM +/- 10% | ROLL LENGTH: | 100 FT |
| CALIPER: | 8 mil +/- 1 | ROLL WIDTHS: | 24", 36", 42", 50", & 60" |
| BRIGHTNESS: | 93 (ISO Blue Whiteness R457) | CORE: | 3" with 2" Adapter |
| WHITENESS: | 150 (CIE Ganz) | PRINT SIDE: | Print Side Out |
| GLOSS MEASUREMENT: | 20 +/- 10% by angle of 60° | INK RECOMMENDATIONS: |  AQUEOUS  LATEX  UV |



This media is designed for digital printing applications using OEM printers with their accompanying OEM ink sets. Although designed for all printers using the aforementioned OEM matching ink sets, actual results may vary depending on printer model, age, print design, environmental conditions, and other factors. Exposure of a print to atmospheric pollutants, or to temperature, humidity, and / or lighting extremes can result in fading, color shifting, or other visual changes. The ideal conditions for printing and storage are a temperature of 70°F ±5°F and relative humidity of 50% RH ±3% RH. Our wide format media is guaranteed against manufacturing flaws and defects and is designed to resist printer jams when used properly. Storage: Up to one year if stored in proper conditions (cool, dry place 50-80°)