



## QM-9BB25G: 9 oz. gloss blackout frontlit fire retardant scrim banner

Unlike most scrim banner on the market, this was developed to be extremely durable and work with Eco-Solvent and UV platforms. Its high tensile strength, makes for a very tear resistant banner. The fire retardant coating allows it to be used in all environments.



### Benefits:

- Fire Retardant
- 500 x 500 Denier
- Scratch Resistant
- Durable

### Applications:

- Frontlit Banners
- Display Systems
- Grommeted Banners
- POP Display

Registered Latex Developer



#### TECHNICAL DATA: QM-9BB25G – 9 OZ. GLOSS BLOCKOUT FRONTLIT FIRE RETARDANT SCRIM BANNER

SURFACE FINISH:	Gloss	OPACITY:	97
BASE MATERIAL:	PVC	DURABILITY:	<i>Indoor:</i> Up to 1 year <i>Outdoor:</i> Up to 6 months
BASE WEIGHT:	(9 oz.) 320 GSM +/- 10%	ROLL LENGTH:	150 FT.
CALIPER:	11 Mil +/- 1	ROLL WIDTHS:	38"
BRIGHTNESS:	78 (ISO Blue Whiteness)	CORE:	3"
WHITENESS:	91 (CIE Ganz)	PRINT SIDE:	Print Side Out
GLOSS MEASUREMENT	40 +/- 10% by angle of 60°	INK RECOMMENDATIONS:	ES ECO-SOLVENT UV UV
STORAGE: Up to six months if stored in proper conditions (cool, dry place 50-80°)			



This media is designed for digital printing applications using OEM printers with their accompanying OEM ink sets. Although designed for all printers using the aforementioned OEM matching ink sets; actual results may vary depending on printer model, age, print design, environmental conditions, and other factors. Exposure of a print to atmospheric pollutants, or to temperature, humidity, and / or lighting extremes can result in fading, color shifting, or other visual changes. The ideal conditions for printing and storage are a temperature of 70°F ±5°F and relative humidity of 50% RH ±3% RH. Our wide format media is guaranteed against manufacturing flaws and defects and is designed to resist printer jams when used properly. Storage: Up to six months if stored in proper conditions (cool, dry place 50-80°)

