



PGSAV: Professional gloss vinyl w/ permanent adhesive

PGSAV is your best option for everyday use. It's bright white surface provides the best color graphics. The water based adhesive provides longer term adhesion. This product is sure to be your go-to for most mounted jobs.



Benefits:

- Bright White
- High Gloss
- Easy Application

Applications:

- Decals
- Flexible or Mounted Signage
- Trade Show Graphics

Registered Latex Developer



TECHNICAL DATA: QM-PGSAV – PROFESSIONAL GLOSS VINYL W/ PERMANENT ADHESIVE

SURFACE FINISH:	Gloss	WHITENESS:	150 (CIE Ganz)
BASE MATERIAL:	PVC	OPACITY:	95
ADHESIVE MATERIAL:	Permanent Water Based Pressure Sensitive Adhesive	GLOSS MEASUREMENT:	28 +/- 10% by angle of 60°
LINER MATERIAL:	PE coated white Wood-pulp Paper	DURABILITY:	Indoor: Up to 1 year Outdoor: Up to 6 months
LINER WEIGHT:	120 GSM +/- 10%	ROLL LENGTH:	150 Ft.
LINER CALIPER:	5 Mil +/- 1	ROLL WIDTHS:	30", 54" & 60"
FACE STOCK WEIGHT:	132 GSM +/- 10%	CORE:	3"
FACE STOCK CALIPER:	5 Mil +/- 1	PRINT SIDE:	Print Side Out
BRIGHTNESS:	96 (ISO Blue Whiteness):	INK RECOMENDATIONS:	ECO-SOLVENT LATEX UV
STORAGE: Up to six months if stored in proper conditions (cool, dry place 50-80°)			



This media is designed for digital printing applications using OEM printers with their accompanying OEM ink sets. Although designed for all printers using the aforementioned OEM matching ink sets; actual results may vary depending on printer model, age, print design, environmental conditions, and other factors. Exposure of a print to atmospheric pollutants, or to temperature, humidity, and / or lighting extremes can result in fading, color shifting, or other visual changes. The ideal conditions for printing and storage are a temperature of 70°F ±5°F and relative humidity of 50% RH ±3% RH. Our wide format media is guaranteed against manufacturing flaws and defects and is designed to resist printer jams when used properly. Storage: Up to one year if stored in proper conditions (cool, dry place 50-80°)

