



QM-SBOBLUX: Hybrid satin lux blackout roll-up film

SBOBLUX is our most popular roll-up display film. This hybrid-semi rigid film offers the durability and stability of PET film along with the economical price of polypropylene. New anti-scratch coating does not require lamination so production time increases. It has the preferred white back and stay-flat properties required for good looking banner stand displays. Use with any of our roll-up banner stands for a complete solution.



Benefits:

- Ultra Durable & Lays Flat
- Lamination Not Needed
- Blockout White Back
- High White Point for Bright Graphics

Applications:

- Roll-up Banner Stands
- Pop-in Display Units
- Trade Show Display

Registered Latex Developer



TECHNICAL DATA: QM-SBOBLUX – HYBRID SATIN LUX BLOCKOUT ROLL-UP FILM

SURFACE FINISH:	Satin	OPACITY:	100
BASE MATERIAL:	Hybrid Film	DURABILITY:	Indoor: Up to 1 year Outdoor: Up to 6 months
BASE WEIGHT:	229 GSM +/- 10%	ROLL LENGTH:	100 FT.
CALIPER:	11 Mil +/- 1	ROLL WIDTHS:	36", 50" & 60"
BRIGHTNESS:	90 (ISO Blue Whiteness)	CORE:	3"
WHITENESS:	93 (CIE Ganz)	PRINT SIDE:	Print Side Out
GLOSS MEASUREMENT	13 +/- 10% by angle of 60°	INK RECOMMENDATIONS:	Eco Solvent Latex UV



This media is designed for digital printing applications using OEM printers with their accompanying OEM ink sets. Although designed for all printers using the aforementioned OEM matching ink sets; actual results may vary depending on printer model, age, print design, environmental conditions, and other factors. Exposure of a print to atmospheric pollutants, or to temperature, humidity, and / or lighting extremes can result in fading, color shifting, or other visual changes. The ideal conditions for printing and storage are a temperature of 70°F ±5°F and relative humidity of 50% RH ±3% RH. Our wide format media is guaranteed against manufacturing flaws and defects and is designed to resist printer jams when used properly. Storage: Up to one year if stored in proper conditions (cool, dry place 50-80°)

