



QM-SMARTDOT: WR repositionable PET window film w/ dot adhesive

SMARTDOT is matte coated for a smooth finish and allows for heavy ink saturation for sharp, vivid images. The quick dry performance will keep production moving, while minimizing overhead and maximizing profits. The dot adhesive will make your graphic shine on any window. Dimensionally stable PET film ensures that your window graphics do not shrink or peel off over time.



Benefits:

- Matte Finish
- Water Resistant
- Durable
- High Definition Ink Retention
- Non-Shrink Dimensionally Stable

Applications:

- Window Displays
- Contour Cutting
- POP Signage

Registered Latex Developer



TECHNICAL DATA: QM-SMARTDOT – WR REPOSITIONABLE PET WINDOW FILM W/ DOT ADHESIVE

SURFACE FINISH:	Matte	OPACITY:	80
BASE MATERIAL:	PET	DURABILITY:	<i>Indoor:</i> Up to 1 year <i>Outdoor:</i> Up to 6 months
BASE WEIGHT:	135 GSM +/- 10%	ROLL LENGTH:	100 FT.
CALIPER:	8 Mil +/- 1	ROLL WIDTHS:	36" & 50"
BRIGHTNESS:	72 (ISO Blue Whiteness)	CORE:	3"
WHITENESS:	97 (CIE Ganz)	PRINT SIDE:	Print Side Out
GLOSS MEASUREMENT	7 +/- 10% by angle of 60°	INK RECOMMENDATIONS:	AQUEOUS LATEX UV



This media is designed for digital printing applications using OEM printers with their accompanying OEM ink sets. Although designed for all printers using the aforementioned OEM matching ink sets; actual results may vary depending on printer model, age, print design, environmental conditions, and other factors. Exposure of a print to atmospheric pollutants, or to temperature, humidity, and / or lighting extremes can result in fading, color shifting, or other visual changes. The ideal conditions for printing and storage are a temperature of 70°F ±5°F and relative humidity of 50% RH ±3% RH. Our wide format media is guaranteed against manufacturing flaws and defects and is designed to resist printer jams when used properly. Storage: Up to one year if stored in proper conditions (cool, dry place 50-80°)

