



QM-TAC: Matte WR vinyl w/ grey removable adhesive for smooth surfaces

This premium 6 mil vinyl has a gray removable adhesive and a lay-flat liner for easy application and removal. Its bright white, matte porous coating keeps the graphic vibrant and water resistant. Use with our millennium laminates for additional protection. Good outdoors for up to 3 months.



Benefits:

- Easy, No Residue Removal for Up to 6 months
- Good Opacity & Whiteness
- Water Resistant

Applications:

- Short-term Exterior Window
- Window & Smooth Surface Display
- Decals & Labels for Window & Smooth Surfaces

Registered Latex Developer

TECHNICAL DATA: QM-TAC — MATTE WR VINYL W/ GREY REMOVABLE ADHESIVE FOR SMOOTH SURFACES

| | | | |
|---|--|----------------------|--|
| SURFACE FINISH: | Matte | WHITENESS: | 150 (CIE Ganz) |
| BASE MATERIAL: | PVC | OPACITY: | 99 |
| ADHESIVE MATERIAL: | Acrylic Adhesive, Medium Tack Removable Adhesive | GLOSS MEASUREMENT: | 3 +/- 10% by angle of 60° |
| LINER MATERIAL: | Kraft with double PE coated, matte back finish | DURABILITY: | Indoor: Up to 1 year Outdoor: Up to 6 months |
| LINER WEIGHT: | 160 GSM +/- 10% | ROLL LENGTH: | 100 FT. |
| LINER CALIPER: | 6 Mil +/- 1 | ROLL WIDTHS: | 36" |
| FACE STOCK WEIGHT: | 180 GSM +/- 10% | CORE: | 3" with 2" adapter |
| FACE STOCK CALIPER: | 6 Mil +/- 1 | PRINT SIDE: | Print Side Out |
| BRIGHTNESS: | 100 (ISO Blue Whiteness) | INK RECOMMENDATIONS: | AQUEOUS |
| STORAGE: Up to six months if stored in proper conditions (cool, dry place 50-80°) | | | |



This media is designed for digital printing applications using OEM printers with their accompanying OEM ink sets. Although designed for all printers using the aforementioned OEM matching ink sets; actual results may vary depending on printer model, age, print design, environmental conditions, and other factors. Exposure of a print to atmospheric pollutants, or to temperature, humidity, and / or lighting extremes can result in fading, color shifting, or other visual changes. The ideal conditions for printing and storage are a temperature of 70°F ±5°F and relative humidity of 50% RH ±3% RH. Our wide format media is guaranteed against manufacturing flaws and defects and is designed to resist printer jams when used properly. Storage: Up to six months if stored in proper conditions (cool, dry place 50-80°)

