



QM-WRTYK: Matte WR instant dry tyvek

Que Media Tyvek® by Dupont® is durable, tear resistant and extremely lightweight. Ultra smooth surface for HD graphics and rich color gamut. Our coating is formulated specifically for high speed print systems and is approved for the Hp PageWide XL. Super fast dry times to keep up with the output of these new print systems.



Benefits:

- Ultra Smooth
- Extremely Durable
- Smudge Resistant
- Easy to Handle

Applications:

- Posters & Presentations
- Lightweight Banners
- Trade Show & Event Displays
- POP & Retail Display

TECHNICAL DATA: QM-WRTVK – MATTE WR INSTANT DRY TYVEK

| | | | |
|--------------------|---------------------------|----------------------|---|
| SURFACE FINISH: | Matte | OPACITY: | 92 |
| BASE MATERIAL: | Hybrid Film | DURABILITY: | <i>Indoor: Up to 1 year Outdoor: Up to 6 months</i> |
| BASE WEIGHT: | 70 GSM +/- 10% | ROLL LENGTH: | 100 FT. |
| CALIPER: | 8 Mil +/- 1 | ROLL WIDTHS: | 36" |
| BRIGHTNESS: | 103 (ISO Blue Whiteness) | CORE: | 3" |
| WHITENESS: | 138 (CIE Ganz) | PRINT SIDE: | Print Side Out |
| GLOSS MEASUREMENT: | 2 +/- 10% by angle of 60° | INK RECOMMENDATIONS: | AQUEOUS LATEX UV |



This media is designed for digital printing applications using OEM printers with their accompanying OEM ink sets. Although designed for all printers using the aforementioned OEM matching ink sets; actual results may vary depending on printer model, age, print design, environmental conditions, and other factors. Exposure of a print to atmospheric pollutants, or to temperature, humidity, and / or lighting extremes can result in fading, color shifting, or other visual changes. The ideal conditions for printing and storage are a temperature of 70°F ±5°F and relative humidity of 50% RH ±3% RH. Our wide format media is guaranteed against manufacturing flaws and defects and is designed to resist printer jams when used properly. Storage: Up to one year if stored in proper conditions (cool, dry place 50-80°)

