



**QM-PPRAD:**

Matte polypropylene blackout film with removable adhesive

This PVC-free film has a premium quality matte top coating to enhance color and resolution. No shrinkage or curling. Grey back creates a block-out barrier for maximum opacity.



**Benefits:**

- Premium Top Coat
- Smooth Non-Glare Finish
- No Residue When Removed
- Blockout Grey Backside

**Applications:**

- Advertising/Messaging
- Window Signage
- Smooth, Flat Surface
- Contour Cut

Registered Latex Developer



**TECHNICAL DATA**

SURFACE FINISH:	Matte	WHITENESS:	88 (CIE Ganz)
BASE MATERIAL:	Polypropylene	GLOSS MEASUREMENT:	3 +/- 10% by angle of 60°
ADHESIVE:	Removable Solvent Acrylic	OPACITY:	93
LINER WIEGHT:	111 GSM +/- 10%	DURABILITY:	Indoor: Up to 1 year Outdoor: 6 months
LINER THICKNESS:	5 Mil +/- 1	ROLL LENGTH:	100 FT.
LINER MATERIAL:	Double Coated PE Paper	ROLL WIDTHS:	36"
FACE STOCK WEIGHT:	111 GSM +/- 10%	CORE:	3"
FACE STOCK CALIPER:	5 Mil	PRINT SIDE:	Print Side Out
BRIGHTNESS:	100 (ISO Blue Whiteness)	INK RECOMMENDATIONS:	AQUEOUS  UV  LATEX



This media is designed for digital printing applications using OEM printers with their accompanying OEM ink sets. Although designed for all printers using the aforementioned OEM matching ink sets; actual results may vary depending on printer model, age, print design, environmental conditions, and other factors. Exposure of a print to atmospheric pollutants, or to temperature, humidity, and / or lighting extremes can result in fading, color shifting, or other visual changes. The ideal conditions for printing and storage are a temperature of 70°F ±5°F and relative humidity of 50% RH ±3% RH. Our wide format media is guaranteed against manufacturing flaws and defects and is designed to resist printer jams when used properly. Storage: Up to one year if stored in proper conditions (cool, dry place 50-80°)

