



QM-TRITEXT7: Satin Hybrid Media

A very unique product. Slightly softer than polypropylene, but has much more strength and durability, virtually tear-proof. The most economical alternative to Tyvek, Teslin, and other tear strength products, that also works with multiple print platforms. This tree-free and PVC-free media truly redefines film with many various applications that require extreme durability.



Benefits:

- Tear Resistant
- Water/Weather Resistant
- Light Weight
- Can be written on with pen, pencil, or sharpie

Applications:

- Wristbands
- Placemats
- Banners, Signs, & Posters
- Maps, Guides, & Blueprints
- Runners Bibs

Registered Latex Developer



TECHNICAL DATA: SATIN HYBRID MEDIA

| | | | |
|-----------------|--------------------------|----------------------|--|
| SURFACE FINISH: | Satin | GLOSS MEASUREMENT: | 6 +/- 10% by angle of 60° |
| MELTING POINT: | 390° F | OPACITY: | 96 |
| BASE WEIGHT: | 140 GSM +/- 10% | DURABILITY: | Indoor: Up to 1 year Outdoor: Up to 6 months |
| CALIPER: | 7 MIL +/- 1 | SHEET SIZES: | 12 x18 in. 13 x19 in. (Special order sizes available.) |
| BRIGHTNESS: | 101 (ISO Blue Whiteness) | PRINT SIDE: | Double Side Printable |
| WHITENESS | 123 (CIE Ganz) | INK RECOMMENDATIONS: | COLOR LASER, INDIGO, DIGITAL PRESS, UV |



This media is designed for digital printing applications using OEM printers with their accompanying OEM ink sets. Although designed for all printers using the aforementioned OEM matching ink sets; actual results may vary depending on printer model, age, print design, environmental conditions, and other factors. Exposure of a print to atmospheric pollutants, or to temperature, humidity, and / or lighting extremes can result in fading, color shifting, or other visual changes. The ideal conditions for printing and storage are a temperature of 70°F ±5°F and relative humidity of 50% RH ±3% RH. Our wide format media is guaranteed against manufacturing flaws and defects and is designed to resist printer jams when used properly. Storage: Up to one year if stored in proper conditions (cool, dry place 50-80°)

