





QM-STIQUE-IT:

Easy-change Base Film (Not for Print)

Make any adhesive product removable with our 'Easy-change' base film. Stubborn adhesive media removal such as aged vinyl that leaves unwanted residue behind is a non-issue with Que Media's exclusive STIQUE-IT Base Film. Easily remove, apply, re-apply or switch out all adhesive backed print medias with ease! Consider the benefits and versatility of STIQUE-IT for your future advertising and promotional space!



Benefits:

- Easily switch-out time sensitive or seasonal graphics, messaging and advertising.
- Effortlessly uninstall permanent, adhesive-backed media.
- Protect interior/exterior wall finishes.
- Eco-friendly and PVC-free!

Applications:

- Retail Cooler Wraps
- Dorms & Institution Walls
- Interior Design/Wall Coverings
- Yard Signs
- Set Design and Flats
- Table Tops
- Elevators

TECHNICAL DATA:			
SURFACE FINISH:	Gloss White	WHITENESS:	N/A (CIE Ganz)
BASE MATERIAL:	Polypropylene	DURABILITY:	1-2 years in ideal conditions
ADHESIVE MATERIAL:	Permanent	STORAGE: Up to 1 year if sto	ored in proper conditions (cool, dry place 50-80°)
LINER MATERIAL:	Embossed Coated Release Paper	ROLL LENGTH:	164 Ft.
LINER WEIGHT:	136 GSM +/- 10%	ROLL WIDTHS:	50"
LINER CALIPER:	6.5 Mil +/- 1	CORE:	3"
FACE STOCK WEIGHT:	125 GSM +/- 10%	PRINT SIDE:	N/A
FACE STOCK CALIPER:	6 Mil +/- 1	INK RECOMMENDATIONS:	N/A
BRIGHTNESS:	N/A (ISO Blue Whiteness)		



This media is designed for digital printing applications using OEM printers with their accompanying OEM ink sets. Although designed for all printers using the aforementioned OEM matching ink sets; actual results may vary depending on printer model, age, print design, environmental conditions, and other factors. Exposure of a print to atmospheric pollutants, or to temperature, humidity, and / or lighting extremes can result in fading, color shifting, or other visual changes. The ideal conditions for printing and storage are a temperature of 70°F ±5°F and relative humidity of 50% RH ±3% RH. Our wide format media is guaranteed against manufacturing flaws and defects and is designed to resist printer jams when used properly. Storage: Up to one year if stored in proper conditions (cool, dry place 50-80°)

