




QM-6040.ECOWV

Perforated vinyl 60/40 ratio w/removable adhesive dual paper liner

The 60/40% perforation pattern allows for the maximum print surface, making it ideal for all retail exterior-mount window graphics requiring small detail and text. Clear adhesive, removable up to one year. The dual perforated paper liner protects printer beds.



Hole Size: 1.5mm - Perf Ratio of 40%



Benefits:

- 60/40% Ratio
- Easy Application
- Removable
- Vivid Graphics
- Reduces Direct Sunlight & Heat

Applications:

- POP Decals
- Retail and Commercial Window Signage
- Acrylic Panels
- Trade Show Graphics



TECHNICAL DATA:

| | | | |
|---|--|----------------------|--|
| SURFACE FINISH: | Gloss | BRIGHTNESS: | 74 (ISO Blue Whiteness) |
| BASE MATERIAL: | PVC | WHITENESS: | 80 (CIE Ganz) |
| BASE SIDE DESCRIPTION: | White Surface/Black Back | GLOSS MEASUREMENT: | 41 +/- 10 by angle of 60° |
| ADHESIVE MATERIAL: | Solvent PSA | DURABILITY: | Indoor: Up to 1 year Outdoor: Up to 6 months |
| LINER MATERIAL: | Perforated Silicon and PE Coating Composit Liner | ROLL LENGTH: | 164 Ft. |
| LINER WEIGHT: | 185 GSM +/- 10% | ROLL WIDTHS: | 54" |
| LINER CALIPER: | 10 Mil +/- 1 | CORE: | 3" |
| FACE STOCK WEIGHT: | 167 GSM +/- 10% | PRINT SIDE: | Print Side Out |
| FACE STOCK CALIPER: | 7 Mil +/- 1 | INK RECOMMENDATIONS: | ES ECO-SOLVENT L LATEX * UV UV |
| STORAGE: Up to six months if stored in proper conditions (cool, dry place 50-80°) | | | |

*Accepts a maximum of 200% ink flow for UV print systems



This media is designed for digital printing applications using OEM printers with their accompanying OEM ink sets. Although designed for all printers using the aforementioned OEM matching ink sets; actual results may vary depending on printer model, age, print design, environmental conditions, and other factors. Exposure of a print to atmospheric pollutants, or to temperature, humidity, and / or lighting extremes can result in fading, color shifting, or other visual changes. The ideal conditions for printing and storage are a temperature of 70°F ±5°F and relative humidity of 50% RH ±3% RH. Our wide format media is guaranteed against manufacturing flaws and defects and is designed to resist printer jams when used properly. Storage: Up to six months if stored in proper conditions (cool, dry place 50-80°)

