

WIDE FORMAT & DIGITAL PRINT MEDIA





QM-CDW:

Economical 3 MIL Matte Paper/PET with Removable Adhesive

This matte finished layered product combines the strength of polyester film with the cost savings of paper. This provides you with a durable, tear resistant adhesive label solution that is cost effective and water resistant. A great PVC-free, shrink resistant option that comes with an easy to use removable adhesive that makes it simple to switch your advertising without any residue being left behind. A perfect solution for any retail environment requiring a durable inexpensive label option.



Benefits:

- Economical
- Tear Resistant, Water and Weather Resistant
- Leaves No Residue
- Light Weight & Stretch Resistant
- Can be written on with pen, pencil, or sharpie

Applications:

- Cooler Door Advertising
- Labels, Decals
- Signs, & Posters



Registered Latex Developer



TECHNICAL DATA: ECONOMICAL 3 MIL MATTE PAPER/PET WITH REMOVABLE ADHESIVE

TEGNINICAE DATA. EGONOMICAE 3 MIE MATTETATENT ET WITT NEMOVADEL ADIESIVE			
SURFACE FINISH:	Matte	WHITENESS	123 (CIE Ganz)
ADHESIVE TYPE:	Removable Acrylic	GLOSS MEASUREMENT:	6 +/- 10% by angle of 60°
¹ MELTING POINT:	390° F	OPACITY:	96
FACE STOCK WEIGHT:	116 GSM +/- 10%	DURABILITY:	Indoor: Up to 1 year Outdoor: Up to 6 months
FACE STOCK CALIPER:	3 MIL +/- 1	SHEET SIZES:	8.5" × 11", 8.5" × 14"
LINER WEIGHT:	130 GSM +/- 10%	PRINT SIDE:	Single Side Printable
LINER CALIPER:	5 MIL +/- 1	INK RECOMMENDATIONS:	COLOR LASER, INDIGO, DIGITAL PRESS, UV
BRIGHTNESS:	101 (ISO Blue Whiteness)		



This media is designed for digital printing applications using OEM printers with their accompanying OEM ink sets. Although designed for all printers using the aforementioned OEM matching ink sets; actual results may vary depending on printer model, age, print design, environmental conditions, and other factors. Exposure of a print to atmospheric pollutants, or to temperature, humidity, and / or lighting extremes can result in fading, color shifting, or other visual changes. The ideal conditions for printing and storage are a temperature of 70°F ±5°F and relative humidity of 50% RH ±3% RH. Our wide format media is guaranteed against manufacturing flaws and defects and is designed to resist printer jams when used properly. Storage: Up to one year if stored in proper conditions (cool, dry place 50-80°)

