



QM-PPGWRADP:

Everyday gloss microporous polypropylene w/permanent adhesive

Designed to be used on applications such as boards, window signs, or any other type of smooth surface for adhesive signage. Its microporous coating gives it the ability to produce photo quality images while maintaining great tear resistance.



Benefits:

- Economical
- Water Resistant
- Wide Color Gamut
- Tear Resistant

Applications:

- Flat Mounting Applications
- Window Signage
- Board & Magnate Material
- Photo Displays

TECHNICAL DATA:

SURFACE FINISH:	Gloss	WHITENESS:	109 (CIE Ganz)
BASE MATERIAL:	Polypropylene	GLOSS MEASUREMENT:	38 +/- 10% by angle of 60°
ADHESIVE MATERIAL:	Clear Acrylic Permanent	OPACITY:	96
LINER MATERIAL:	PET	DURABILITY:	Indoor: Up to 1 year Outdoor: 6 months
LINER WEIGHT:	90 GSM +/- 10%	ROLL LENGTH:	100 FT.
LINER CALIPER:	4 +/- .5 Mil	ROLL WIDTHS:	24", 36", 42", 50", & 60"
FACE STOCK WEIGHT:	165 GSM +/- 10%	CORE:	3" with 2" Adapter
FACE STOCK CALIPER:	9 Mil +/- 1	PRINT SIDE:	Print Side Out
BRIGHTNESS:	90 (ISO Blue Whiteness)	INK RECOMMENDATIONS:	AQUEOUS LATEX UV



This media is designed for digital printing applications using OEM printers with their accompanying OEM ink sets. Although designed for all printers using the aforementioned OEM matching ink sets; actual results may vary depending on printer model, age, print design, environmental conditions, and other factors. Exposure of a print to atmospheric pollutants, or to temperature, humidity, and / or lighting extremes can result in fading, color shifting, or other visual changes. The ideal conditions for printing and storage are a temperature of 70°F ±5°F and relative humidity of 50% RH ±3% RH. Our wide format media is guaranteed against manufacturing flaws and defects and is designed to resist printer jams when used properly. Storage: Up to one year if stored in proper conditions (cool, dry place 50-80°)

