



QM-SPP2P

2 Mil Metalized Polypropylene w/White Liner

This unique highly reflective mirror-like polypropylene comes with a durable permanent adhesive, making it a fantastic choice for any high end retail labelling application. This paper-free and PVC-free media truly redefines standard adhesive film media, providing extreme durability and the added benefit of performing great for die-cutting. Compatible with Dry Toner, Indigo, Digital Press, and all UV printing platforms.



Benefits:

- Highly Reflective Mirror-Like Finish
- Water & Tear Resistant
- Die-cut & Perforation Friendly
- Compliments White Toner/Ink Printing

Applications:

- Die-cut Labels & Seals
- Bottle & Cans
- Decorative Labelling
- Retail/Lab/Shop Labelling
- Stickers/Decals



Registered Latex Developer



TECHNICAL DATA:

| | | | |
|---------------------|----------------------------|----------------------|---|
| SURFACE FINISH: | Highly Reflective Metallic | WHITENESS | N/A (CIE Ganz) |
| ADHESIVE TYPE: | Permanent Acrylic | GLOSS MEASUREMENT: | 99 +/- 10% by angle of 60° |
| MELTING POINT: | 390° F | OPACITY: | 96 |
| FACE STOCK WEIGHT: | 46 GSM +/- 10% | DURABILITY: | Indoor: Up to 1 year Outdoor: Up to 6 months |
| FACE STOCK CALIPER: | 2 MIL +/- 1 | SHEET SIZES: | 8.5 x 11", 8.5 x 14", 11 x 17", 12 x18", 13 x 19" |
| LINER WEIGHT: | 130 GSM +/- 10% | PRINT SIDE: | Single Side Printable |
| LINER CALIPER: | 5 MIL +/- 1 | INK RECOMMENDATIONS: | COLOR LASER, INDIGO, DIGITAL PRESS, UV |
| BRIGHTNESS: | N/A (ISO Blue Whiteness) | | |



This media is designed for digital printing applications using OEM printers with their accompanying OEM ink sets. Although designed for all printers using the aforementioned OEM matching ink sets; actual results may vary depending on printer model, age, print design, environmental conditions, and other factors. Exposure of a print to atmospheric pollutants, or to temperature, humidity, and / or lighting extremes can result in fading, color shifting, or other visual changes. The ideal conditions for printing and storage are a temperature of 70°F ±5°F and relative humidity of 50% RH ±3% RH. Our wide format media is guaranteed against manufacturing flaws and defects and is designed to resist printer jams when used properly. Storage: Up to one year if stored in proper conditions (cool, dry place 50-80°)

