



QM-VSGV6:

Vivid Thick gloss vinyl w/permanent adhesive

QM-VSGV6 is our go-to heavy gloss option for everyday adhesive vinyl applications. It has an extremely bright white points providing excellent color gamut. Along with a double-side PE coated liner making sure your decals stay flat, and feed easily through printers running high heat elements. The solvent acrylic blended permanent adhesive provides longer term adhesion.



Benefits:

- Fluorescent True White Point
- Gloss Finish
- Easy Apply Adhesive
- Thick Shrink Resistant Vinyl
- Economical

Applications:

- Decals
- Flexible Mounted Signage
- Trade Show Graphics
- Indoor/Outdoor Signage
- Contour Cut Graphics/Print & Cut Systems

TECHNICAL DATA

SURFACE FINISH:	Gloss	OPACITY:	98
BASE MATERIAL:	PVC	GLOSS MEASUREMENT:	62 +/- 10% by angle of 60°
ADHESIVE MATERIAL:	Clear solvent acrylic PSA	DURABILITY:	Indoor: Up to 1 year Outdoor: 6 months
LINER MATERIAL:	Double Sided PE Coated Wood Pulp Paper	STORAGE:	Up to 1 year if stored in proper conditions (cool, dry place 50-80°)
LINER WEIGHT:	160 GSM +/- 10%	ROLL LENGTH:	150 Ft.
LINER CALIPER:	6 Mil +/- 1	ROLL WIDTHS:	54"
FACE STOCK WEIGHT:	210 GSM +/- 10%	CORE:	3"
FACE STOCK CALIPER:	6 Mil +/- .5	PRINT SIDE:	Print Side Out
BRIGHTNESS:	98 (ISO Blue Whiteness)	INK RECOMMENDATIONS:	ES ECO-SOLVENT L LATEX UV UV
WHITENESS:	143 (CIE Ganz)		



This media is designed for digital printing applications using OEM printers with their accompanying OEM ink sets. Although designed for all printers using the aforementioned OEM matching ink sets; actual results may vary depending on printer model, age, print design, environmental conditions, and other factors. Exposure of a print to atmospheric pollutants, or to temperature, humidity, and / or lighting extremes can result in fading, color shifting, or other visual changes. The ideal conditions for printing and storage are a temperature of 70°F ±5°F and relative humidity of 50% RH ±3% RH. Our wide format media is guaranteed against manufacturing flaws and defects and is designed to resist printer jams when used properly. Storage: Up to six months if stored in proper conditions (cool, dry place 50-80°)

