



QM-VSMV6:

Vivid thick matte vinyl w/permanent adhesive

QM-VSMV6 is our go-to heavy matte option for everyday adhesive vinyl applications. It has an extremely bright white points providing excellent color gamut. Along with a double-side PE coated liner making sure your decals stay flat, and feed easily through printers running high heat elements. The solvent acrylic blended permanent adhesive provides longer term adhesion.



Benefits:

- Fluorescent True White Point
- Non-glare Matte Finish
- Easy Apply Adhesive
- Thick Shrink Resistant Vinyl
- Economical

Applications:

- Decals
- Flexible Mounted Signage
- Trade Show Graphics
- Indoor/Outdoor Signage
- Contour Cut Graphics/Print & Cut Systems

TECHNICAL DATA

| | | | |
|---------------------|--|----------------------|--|
| SURFACE FINISH: | Matte | OPACITY: | 98 |
| BASE MATERIAL: | PVC | GLOSS MEASUREMENT: | 9 +/- 10% by angle of 60° |
| ADHESIVE MATERIAL: | Clear solvent acrylic PSA | DURABILITY: | Indoor: Up to 1 year Outdoor: 6 months |
| LINER MATERIAL: | Double Sided PE Coated Wood Pulp Paper | STORAGE: | Up to 1 year if stored in proper conditions (cool, dry place 50-80°) |
| LINER WEIGHT: | 160 GSM +/- 10% | ROLL LENGTH: | 150 Ft. |
| LINER CALIPER: | 6 Mil +/- 1 | ROLL WIDTHS: | 54" |
| FACE STOCK WEIGHT: | 210 GSM +/- 10% | CORE: | 3" |
| FACE STOCK CALIPER: | 6 Mil +/- .5 | PRINT SIDE: | Print Side Out |
| BRIGHTNESS: | 98 (ISO Blue Whiteness) | INK RECOMMENDATIONS: | ES ECO-SOLVENT L LATEX UV UV |
| WHITENESS: | 143 (CIE Ganz) | | |



This media is designed for digital printing applications using OEM printers with their accompanying OEM ink sets. Although designed for all printers using the aforementioned OEM matching ink sets; actual results may vary depending on printer model, age, print design, environmental conditions, and other factors. Exposure of a print to atmospheric pollutants, or to temperature, humidity, and / or lighting extremes can result in fading, color shifting, or other visual changes. The ideal conditions for printing and storage are a temperature of 70°F ±5°F and relative humidity of 50% RH ±3% RH. Our wide format media is guaranteed against manufacturing flaws and defects and is designed to resist printer jams when used properly. Storage: Up to six months if stored in proper conditions (cool, dry place 50-80°)

