



QM-SPFSS:

Super heavyweight satin eco-solvent polyester coated fabric

This super heavyweight polyester fabric can be used for a multitude of applications, hanging banners, theater drops, and outdoor signage. Extremely strong tensile strength and top coated with a satin finish. PVC-free and can be recycled if using latex inks.



Benefits:

- 100% Polyester Fabric
- Textured Satin Weave
- Ultra Strong
- Recyclable ♻️

Applications:

- Hanging Banners or Wall Drape
- Roll Up Banners
- Theater Backdrops

Registered Latex Developer



TECHNICAL DATA:

| | | | |
|-------------------|---------------------------|----------------------|--|
| SURFACE FINISH: | Satin | OPACITY: | 82 |
| BASE MATERIAL: | 100% Polyester Fabric | DURABILITY: | Indoor: Up to 1 year Outdoor: 6 months |
| DENIER: | 600 x 600D | ROLL LENGTH: | 100 FT. |
| BASE WEIGHT: | 236 GSM +/- 10% | ROLL WIDTHS: | 36", & 54" |
| CALIPER: | 12 Mil +/- 1 | CORE: | 3" |
| BRIGHTNESS: | 90 (ISO Blue Whiteness) | PRINT SIDE: | Print Side Out |
| WHITENESS: | 85 (CIE Ganz) | INK RECOMMENDATIONS: | ES ECO-SOLVENT L LATEX UV UV |
| GLOSS MEASUREMENT | 8 +/- 10% by angle of 60° | | |



This media is designed for digital printing applications using OEM printers with their accompanying OEM ink sets. Although designed for all printers using the aforementioned OEM matching ink sets; actual results may vary depending on printer model, age, print design, environmental conditions, and other factors. Exposure of a print to atmospheric pollutants, or to temperature, humidity, and / or lighting extremes can result in fading, color shifting, or other visual changes. The ideal conditions for printing and storage are a temperature of 70°F ±5°F and relative humidity of 50% RH ±3% RH. Our wide format media is guaranteed against manufacturing flaws and defects and is designed to resist printer jams when used properly. Storage: Up to one year if stored in proper conditions (cool, dry place 50-80°)

