



FFSC (901SSJ):
Satin Cotton/Polyester Inkjet Canvas

Ideal for high-end photo and fine art reproduction. This satin canvas will deliver the highest dmax levels and widest range color gamut when used with photo black inks. It does not require varnishing which increases production time. This canvas is one of Fredrix's most popular products.



Benefits:

- 35% Cotton/65% Polyester
- Crack Resistant Coating
- No Coating/Varnish Needed
- High-end Fine Art Reproduction
- Satin Coating

Applications:

- Museum & Gallery Prints
- Home Décor Printing
- Photo Reproduction
- Gallery Stretched Giclee's
- Framed Art

Registered Latex Developer



TECHNICAL DATA:

SURFACE FINISH:	Satin, Medium Texture	GLOSS MEASUREMENT:	5+/- 10% by angle of 60°
BASE MATERIAL:	35% Cotton/65% Polyester	LONGEVITY:	25 Years
BASE WEIGHT:	385 GSM +/- 10%	ROLL LENGTH:	75 FT.
CALIPER:	18 Mil +/- 1	ROLL WIDTHS:	54" & 60"
FABRIC WEAVE:	2:1	CORE:	3"
BRIGHTNESS:	100 (ISO Blue Whiteness)	PRINT SIDE:	Print Side Out
WHITENESS:	122 (CIE Ganz)	INK RECOMMENDATIONS:	ECOSOLVENT LATEX UV



This media is designed for digital printing applications using OEM printers with their accompanying OEM ink sets. Although designed for all printers using the aforementioned OEM matching ink sets; actual results may vary depending on printer model, age, print design, environmental conditions, and other factors. Exposure of a print to atmospheric pollutants, or to temperature, humidity, and / or lighting extremes can result in fading, color shifting, or other visual changes. The ideal conditions for printing and storage are a temperature of 70°F ±5°F and relative humidity of 50% RH ±3% RH. Our wide format media is guaranteed against manufacturing flaws and defects and is designed to resist printer jams when used properly. Storage: Up to one year if stored in proper conditions (cool, dry place 50-80°)

