





## **QM-SPPMR:**

## Matte Blockout Polypropylene with Removable/ Repositionable Adhesive

Equipped with a solvent acrylic removable adhesive, making it a perfect choice for blockout window graphics, and other removable adhesive-backed applications. Designed to be a longer lasting alternative to traditional monomeric window graphic media, say good bye to edge curl over time! Developed as a weather-resistant, tear resistant, shrink resistant alternative PVC vinyl. Economical and PVC-Free, this product is excellent choice for removable graphics, and will leave no residue behind after removal.



## **Benefits:**

- PVC-Free
- Curl Resistant
- Longer Lasting than Monomeric PVC
- Blockout Media
- Easy to remove, no residue
- High Density Polypropylene with med/low tack adhesive

## **Applications:**

- Shrink Resistant Window Graphics
- All Weather removable Adhesive Matte Film
- Conditions Requiring Blockout

Registered Latex Develope





TECHNICAL DATA:				
SURFACE FINISH:	Matte	OPA	ACITY:	99
BASE MATERIAL:	Polypropylene	GLC	OSS MEASUREMENT:	9 +/- 10% by angle of 60°
ADHESIVE MATERIAL:	Removable/Repositionable Adhesive	DUF	RABILITY:	Indoor: Up to 1 year. Outdoor: Up to 6 months
LINER MATERIAL:	Clear Polypropylene	STO	RAGE: Up to 1 year if sto	ored in proper conditions (cool, dry place 50-80°)
LINER WEIGHT:	60 GSM +/-10%	ROL	LL LENGTH:	100 Ft.
LINER CALIPER:	3 Mil +/- 1	ROL	LL WIDTHS:	54"
FACE STOCK WEIGHT:	230 GSM +/- 10%	COF	RE:	3"
FACE STOCK CALIPER:	7 Mil +/- 1	PRII	NT SIDE:	Print Side Out
BRIGHTNESS:	91 (ISO Blue Whiteness)	INK	RECOMMENDATIONS:	ES ECO-SOLVENT L LATEX UV UV
WHITENESS:	92 (CIE Ganz)			



This media is designed for digital printing applications using OEM printers with their accompanying OEM ink sets. Although designed for all printers using the aforementioned OEM matching ink sets; actual results may vary depending on printer model, age, print design, environmental conditions, and other factors. Exposure of a print to atmospheric pollutants, or to temperature, humidity, and / or lighting extremes can result in fading, color shifting, or other visual changes. The ideal conditions for printing and storage are a temperature of 70°F ±5°F and relative humidity of 50% RH ±3% RH. Our wide format media is guaranteed against manufacturing flaws and defects and is designed to resist printer jams when used properly. Storage: Up to one year if stored in proper conditions (cool, dry place 50-80°)

